

ASHLEY SLING, INC.



ASI-TFS-1 (C) Transformer Sling - Single Adjustable

This adjustable, load-rated two-eye lifting sling has a permanent eye splice at one end and an adjustable eye at the other end, which allows it to adapt to loads of various sizes. The adjustment allows snug lifting control and minimizes the number of fixed leg slings required. Each sling is tagged with a capacity.

- A permanent eye splice at one and adjustable eye at the other
- Adapts to various loads
- Minimizes the number of fixed legs slings required
- Tagged with capacity



	4	SPECIFICAT	*RATED CAPACITIES				
PART NUMBER	SIZE INCHES	COLOR	APPOX. WEIGHT	MIN. LENGTH WITH 1-1/2" EYES	VERTICAL	CHOKER	90° V.BASKET
400-07300	1/2"	BLUE	1.2 LBS.	**2 FT. TO 4 FT.	2,200 LBS.	1,700 LBS	4,400 LBS.
400-07320	5/8"	RED	1.7 LBS.	**2 FT. TO 4 FT.	3,200 LBS.	2,560 LBS	6,400 LBS.
400-07340	3/4"	GREEN	2.8 LBS	**2 FT. TO 4 FT.	4,200 LBS.	3,380 LBS	8,400 LBS.

* Rated capacities are for a sling in vertical lift use. ** Custom length for your application are also available.

Example of 3/4 Inch tag.

0 I VERTICAL		0 0 BASKET	Part No:	3/4" DBL TR/	ANSFORMER SLING		ASHLEY
0 VERTICAL	0 CHOKER		SN:	000000-001-	001		A SLING
4200 LBS	3380 LBS	8400 LBS	Length:	48 INCH	TENEX	U.S.A.	(\mathbf{S}) (\mathbf{I}) INC.