



# ASHLEY SLING, INC.



## PowerLift® Magnets

These compact yet powerful Rare Earth permanent lift magnets can be used on flat or round surfaces and contain an internal release On/Off device that does not contact or damage the surface of the part being lifted. Permanent magnetic lifts eliminate the fear of dropping the load being lifted due to power failures.

The locking system is performed by first pulling on the handle to release the lock pin, then rotating the handle to the desired position. The locking feature prevents the handle from being bumped partially "On" and avoids giving the operator a false feeling that the magnet is holding safely.

### Features

- On/Off Rare Earth Permanent Magnet
- Handle locks in both On and Off position
- Lifts flat or round loads (see chart below)
- Easy internal manual release does not contact the load
- RFID Enabled
- Heat resistant up to 180°F (82°C)
- 3:1 Design Factor
- **CONFORMS TO ASME B30.20 STANDARDS**



Picture above: A customized version of IMI's Vertical Lift Adaptor featuring two PowerLift® magnets, designed to lift ferrous metal from horizontal to vertical orientation or vice versa. Adjustable for various widths, thicknesses and shapes. Ask for Tech Sheet MG-02G for specifications.

Model No.	Lift		Overall		Magnet			Handle		Bail		
	LBS	KG	Ht. (in)	Ln. (in)	Ht. (in)	Wd. (in)	Ln. (in)	Ln. (in)	Th. (in)	Ht. (in)	Wd. (in)	Wt. (lbs)
PNL0250	250	113	6-5/8	5	2-5/8	2-5/8	3-5/8	5-7/8	3/16	1-3/8	1-1/2	7
PNL0800	800	363	8-7/8	7-7/8	3-7/8	3-5/8	6-3/8	6-7/8	1/2	2-3/8	1-3/4	21
PNL1600	1600	726	8-7/8	10-3/4	4-3/4	4-7/8	9-1/8	6-3/4	5/8	3-1/2	2-1/4	51
PNL2500	2500	1134	8-7/8	12-5/8	6-1/2	7-1/8	10-5/8	10-1/8	3/4	4-3/4	3-3/4	122
PNL5000	5000	2268	18	16-1/2	8-3/8	9-1/4	14-7/8	16-3/4	7/8	6	4-3/4	288
PNL6600	6600	2993	22-1/4	20	10-1/4	11-1/4	18-1/16	20-5/8	1-7/16	7-1/4	5-3/4	485

Model No.	Lifting Value in lbs (kg) & *Max Sheet Length Due To Sag For Material Thickness For Single Magnet Use							Round Lifting Applications		
	1/4" (6' Lg)	3/8" (8' Lg)	1/2" (8' Lg)	3/4" (8' Lg)	1" (10' Lg)	2" (10' Lg)	3" (10' Lg)	Lift - lbs (kg)	Min. Dia. (in)	Min. Th. (in)
PNL0250	180 (81)	250 (113)	250 (113)	250 (113)	250 (113)	250 (113)	250 (113)	125 (57)	2	1/2
PNL0800	270 (122)	500 (226)	615 (279)	800 (363)	800 (363)	800 (363)	800 (363)	400 (181)	3	1/2
PNL1600	CF	CF	800 (362)	1600 (726)	1600 (726)	1600 (726)	1600 (726)	800 (363)	4	1
PNL2500	NA	NA	CF	CF	1490 (675)	2500 (1134)	2500 (1134)	1250 (567)	5	2
PNL5000	NA	NA	NA	NA	CF	2625 (1190)	5000 (2268)	2500 (1134)	14	4
PNL6600	NA	NA	NA	NA	NA	NA	6600 (2993)	3300 (1496)	CF	CF

**NOTE:** Lifting Values for the PowerLift® Magnets are stated at 33% of the actual value. We recommend when lifting sheets over 8', use 2 or more lifts on a spreader bar to prevent sheet flexing, sagging or peel-off. Thin material is susceptible to magnetic bleed through, resulting in two sheets being lifted at once. Round Item Lifting Values are based on ideal conditions. Pipe length, wall thickness, diameter and surface condition can all affect the magnet's performance. Please consult the factory before specifying these magnets for use on round materials. \*These maximum sheet lengths are selected due to the sag characteristics of the specified sheet. The item to be lifted must cover the entire length and width of the magnetic poles to properly engage and release the part. CF = Consult Factory NA = Not Applicable (Magnets listed will not turn "ON" on specified material thicknesses.)